

LA -- 1224

CIC-14 REPORT COLLECTION
**REPRODUCTION
COPY**

C. 13


LOS ALAMOS SCIENTIFIC LABORATORY

OF THE

UNIVERSITY OF CALIFORNIA

CONTRACT W-7405-ENG. 36 WITH

U. S. ATOMIC ENERGY COMMISSION



c. 18

LOS ALAMOS SCIENTIFIC LABORATORY
of
THE UNIVERSITY OF CALIFORNIA

March 19, 1951

Series A

LA-1224

THE DENSITIES OF LIQUID TRITIUM, 20.6° TO 29° K (1)

Work done by:

E. R. Grilly

Report written by:

E. R. Grilly

(1) This paper is based on work performed under University of California contract with the Atomic Energy Commission.

Physics

LOS ALAMOS NATL. LAB. LIBS.
3 9338 00310 7488

PHYSICS

MAY 19 1951

LA 1224

Los Alamos

20

Project Distribution

Argonne National Laboratory	12
Armed Forces Special Weapons Project	1
Atomic Energy Commission, Washington	6
Battelle Memorial Institute	1
Brush Beryllium Company	1
Brookhaven National Laboratory	4
Bureau of Medicine and Surgery	1
Bureau of Ships	1
Carbide and Carbon Chemicals Division (K-25 Plant)	4
Columbia University (J. R. Dunning)	1
Columbia University (G. Failla)	1
General Electric, Richland	4
Idaho Operations Office	4
Iowa State College	2
Kansas City Operations Branch	1
Kellex Corporation	1
Kirtland Air Force Base	2
Knolls Atomic Power Laboratory	4
Mallinckrodt Chemical Works	1
Massachusetts Institute of Technology (A. Gaudin)	1
Massachusetts Institute of Technology (A. R. Kaufmann)	1
Mound Laboratory	3
National Advisory Committee for Aeronautics	1
National Bureau of Standards (R. D. Huntoon)	1
Naval Medical Research Institute	1
Naval Radiological Defense Laboratory	2
New Brunswick Laboratory	1
New York Operations Office	3
North American Aviation, Inc.	1
Oak Ridge National Laboratory (X-10 Site)	8
Oak Ridge National Laboratory (Y-12 Site)	4
Patent Branch, Washington	1
RAND Corporation	1
Sandia Corporation	1
Santa Fe Operations Office	1
Technical Information Service, Oak Ridge	75
USAF, NEPA Office	3
U. S. Geological Survey (T. B. Nolan)	2

PHYSICS

LA 1224

Project Distribution - Continued

U. S. Public Health Service	2
University of California at Los Angeles	1
University of California Radiation Laboratory	5
University of Rochester	2
University of Washington	1
Western Reserve University	1
Westinghouse Electric Corporation	4

Supplementary Distribution

Atomic Energy Project, Chalk River	4
Chief of Naval Research	1
H. K. Ferguson Company	1
Harshaw Chemical Company	1
Isotopes Division (Mr. McCormick)	1
Library of Congress, Acquisition Department (J.W. Corrm)	2
National Bureau of Standards	1
National Research Council, Ottawa	1
Naval Research Laboratory	1
Nevis Cyclotron Laboratories	2
Nucleonics	1
Oak Ridge Institute of Nuclear Studies	2
United Kingdom Scientific Mission (M. Greenhill)	10
USAF, Eglin Air Force Base (Technical Library)	1
USAF, Wright-Patterson Air Force Base (Rodney Nudenberg)	1
USAF, Wright-Patterson Air Force Base (CADO)	5
U. S. Army, Army Field Forces (Captain James Kerr)	1
U. S. Army, Atomic Energy Branch (Lt. Col. A. W. Betts)	1
U. S. Army, Director of Operations Research (Dr. Ellis Johnson)	1
U. S. Army, Office, Chief of Ordnance (Col. A. R. Del Campo)	1
U. S. Army, Office of the Chief Signal Officer (Curtis T. Clayton thru Major George C. Hunt)	2
U. S. Army, Technical Command (Col. J. H. Rothschild Attn: Technical Library)	3
UT-AEC Agricultural Research Program (Charles S. Hobbs)	1

THE DENSITIES OF LIQUID TRITIUM, 20.6° TO 29° K

Abstract

Most of a 70 cc (STP) sample of tritium (containing 2.0% HT) was liquefied in a Pyrex bulb of 58 mm³ capacity between two fixed marks. The amount of gas used for this filling gave the difference between liquid and gas density. The results were corrected for gas density and for the presence of HT.

THE TRITIUM SAMPLE

For this work 70 cc (STP) of tritium was used. The source, purification, and storage have been described elsewhere.⁽²⁾ The gas used

⁽²⁾ E. R. Grilly, J. Am. Chem. Soc. 73, 843 (1951).

in the present work contained 2.0% HT and negligible amounts of other constituents, such as H₂, air, and tritocarbons, all determined mass spectrometrically.

THE APPARATUS

This was essentially the same as that used in the vapor pressure measurements.⁽²⁾ In addition, there were provisions for measuring accurately the amounts of gas and of liquid. For the former, the gas was kept under constant volume, constant temperature, and variable pressure, or approximately 255 cc, 25° C, and 0 to 230 mmHg, respectively. The Pyrex liquid bulb consisted of a 17 mm length of 2 mm I.D. tubing, above and below which were regions narrowed down to 0.4 mm I.D. Inked reference marks for the liquid levels, "empty" and "full," were put on the narrow regions. The bulb was observed through a traveling microscope. The bulb volume was calibrated with liquid hydrogen at 19.5° K, the average of six determinations giving a volume of 57.80 mm³ with a mean deviation of $\pm 0.06\%$. Volume determinations were also made between 14° and 22.8°, but no consistent variation was observed. The liquid hydrogen molar volumes below 20.4° were taken from Scott and

Brickwedde,⁽³⁾ and those above 20.4°, from Woolley, Scott, and Brickwedde,⁽⁴⁾

(3) R. B. Scott and F. G. Brickwedde, J. Research Natl. Bur. Standards, 19, 237 (1937).

(4) H. W. Woolley, R. B. Scott, and F. G. Brickwedde, ibid., 41, 379-475 (1948).

who recomputed the results of Mathias, Crommelin, and Onnes.⁽⁵⁾ At 19.500° K the value used was 28.021 cc/mole.

(5) E. Mathias, C. A. Crommelin, and H. Kamerlingh Onnes, Comm. Leiden, 154b (1921).

PROCEDURE

The Toepler pump was used to transfer low-pressure gas into the condensing tube so that the liquid level just came to the bottom mark. The amount of gas left on the other side of the pump was measured by noting the pressure. More gas was liquefied until the upper mark was reached. Bulb immersion in the bath was kept 1 cm above the mark by raising the dewar. Again the amount of gas left was measured. The amount of gas (in moles) used to fill the liquid bulb divided by the bulb volume (between the marks) gives the difference between liquid and gas densities. The gas densities were calculated as previously⁽²⁾ and amounted to a maximum correction of 3.6%. To make a slight (0.3%) correction for the

2.0% HT, linearity between mole fraction and molar volume was assumed, and the molar volume of HT was taken equal to that of D₂.

RESULTS

As a check, the density of deuterium at 19.48°K was determined (after correcting for 0.72% HD) to be 42.89 mole/liter, 0.2% higher than the result of Clusius and Bartholome'.⁽⁶⁾

⁽⁶⁾K. Clusius and E. Bartholome, Z. physik Chem. [B] 30, 237 (1935).

Table I gives the tritium results as follows: the direct measurements on liquid density minus gas density, the calculated gas densities; the liquid densities after correcting for 2.0% HT; the deviations of the final densities from a smooth curve. Table II gives smoothed tritium densities at several temperatures, from the triple point to 29°K.

TABLE I
MOLAR DENSITIES OF LIQUID TRITIUM

T (°K)	ρ liq (mole/liter)	ρ ^(a) gas	ρ gas	ρ ^(b) liq	Dev. from curve
20.61	45.17		0.13	45.39	0.04
22.50	43.97		.16	44.21	- .01
22.99	43.51		.29	43.88	- .04
23.59	43.11		.35	43.55	.00
24.41	42.49		.44	43.01	- .01
24.72	42.24		.48	42.81	- .02
25.66	41.53		.62	42.25	.03
26.36	40.91		.73	41.74	.00
27.09	40.17		.87	41.14	- .05
28.32	39.06		1.14	40.31	.07
29.13	38.02		1.37	39.49	- .06

(a) With 2.0% HT present.

(b) Corrected to 0.0% HT.

TABLE II
SMOOTHED MOLAR DENSITIES OF LIQUID TRITIUM

T (°K)	ρ (mole/liter)	T (°K)	ρ (mole/liter)
20.62	45.35	25	42.65
21	45.12	26	41.98
22	44.52	27	41.26
23	43.91	28	40.48
24	43.29	29	39.66

ACCURACY

Error analysis shows the following possible contributions to $\rho_{\text{liq}} - \rho_{\text{gas}}$ values (first as direct units, then as error per cent):

(a) missing a liquid level mark, 0.2 mm = 0.04%; (b) temperature of the bath, $0.003^\circ = 0.005\%$; (c) temperature of the liquid tritium being above the bath temperature due to radioactive heat, $0.006^\circ = 0.01\%$; (d) temperature in the gas measuring system, $0.1^\circ = 0.03\%$; (e) pressure of the gas, 0.1 mmHg = 0.04%; (f) volume of the gas, 0.05 cc = 0.02%.

These give a maximum error of $\pm 0.18\%$ if additive or a "probable" error of $\pm 0.08\%$ if random. The gas densities should be accurate to 0.1% in the best case (lowest temperature) and to 1% in the worst, contributing 0.000% and 0.04% errors, respectively. Finally, the HT correction should be reliable to 3%, contributing 0.01% error. Summarizing, the liquid density maximum error should be 0.23% for the worst case.

DOCUMENT ROOM

REC. FROM LA

DATE 5-4-51

REC. NO. REC. _____